

Material Safety Data Sheet (MSDS)- **N-BUTANOL**

1. Product Identification

Synonyms : 1-Butanol; propyl carbinol; butanol; n-butyl alcohol
CAS No. : 71-36-3
Molecular Weight : 74.12
Chemical Formula : CH₃(CH₂)₂CH₂OH

COMPANY IDENTIFICATION

Supplier: **Pon Pure Chemicals Group**
CHENNAI, TAMILNADU, INDIA

24 Hour Health Emergency (91) 8939878447
(91) 9444038694

Transportation Emergency Phone (91) 8939768680

Company Name	Place	EMERGENCY TELEPHONE NUMBER
Pon Pure Chemicals Group	India	Day Emergency – 044-26161803-26161809

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
N-Butyl Alcohol	71-36-3	99 - 100%	Yes

3. Hazards Identification Emergency Overview

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY AFFECT LIVER AND KIDNEYS.

Health Rating : 2 - Moderate (Life)

Flammability Rating : 2 - Moderate

Reactivity Rating : 1 - Slight

Contact Rating : 3 - Severe (Life)

Lab Protective Equip : GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD;
PROPER GLOVES; CLASS B EXTINGUISHER

Storage Color Code : Red (Flammable)

Potential Health Effects

Inhalation:

Butyl alcohols have produced few cases of poisoning in industry because of their low volatility. Causes irritation to upper respiratory tract. Difficult breathing, coughing, headache, dizziness, and drowsiness may occur. May be absorbed into the bloodstream with symptoms similar to ingestion.

Ingestion:

May have narcotic effect. May cause abdominal pain, nausea, headache, dizziness, and diarrhea. Large doses may affect kidneys and liver. May affect hearing. Estimated mean lethal dose is 3 - 7 ounces.

Skin Contact:

An irritant to the skin, causing a loss of natural oils. Can be absorbed through skin with symptoms paralleling those from ingestion.

Eye Contact:

Vapors can be irritating, causing tearing and pain. Splashes cause inflammation and blurred vision.

Chronic Exposure:

Prolonged skin contact may cause drying and cracking of skin. Hearing loss has been reported in workers chronically exposed to butyl alcohol. May affect sense of balance, liver and kidneys.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician.

Skin Contact:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point : 37C (99F) CC

Auto ignition temperature : 343C (649F)

Flammable limits in air % by volume: LEL: 1.4; UEL: 11.2

Flammable. Dangerous fire hazard when exposed to heat or flame.

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back.

Sensitive to static discharge.

Fire Extinguishing Media:

Dry chemical, foam or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Water may be used to flush spills away from exposures and to dilute spills to non-flammable mixtures.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment,

including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

- OSHA Permissible Exposure Limit (PEL) :100 ppm
- ACGIH Threshold Limit Value (TLV) :20 ppm (TWA)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a full face piece respirator with organic vapor cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. WARNING: Air purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

- Appearance** : Clear, colorless solution.
- Odor** : Strong characteristic, mildly alcoholic odor.
- Solubility** : 9 mL/100 mL water @ 25C
- Specific Gravity** : 0.81 @ 20C/4C
- pH** : No information found.
- % Volatiles by volume @ 21C (70F):** 100
- Boiling Point** : 118C (244F)

Melting Point : -89C (-128F)
Vapor Density (Air=1) : 2.6
Vapor Pressure (mm Hg) : 5 @ 20C (68F)
Evaporation Rate (BuAc=1): 0.46

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Strong oxidizers, strong mineral acids, halogens, aluminum, chromium trioxide, alkali metals.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Oral rat LD50: 790 mg/kg; inhalation rat LC50: 8000 ppm/4H; skin rabbit LD50: 3400 mg/kg; irritation, standard Draize, skin, rabbit, 20 mg/24H moderate; irritation, standard Draize, eye, rabbit, 2 mg/24H severe; investigated as a mutagen, reproductive effector.

-----\Cancer Lists\-----

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
------------	-------	-------------	---------------

-----	----	-----	-----
-------	------	-------	-------

N-Butyl Alcohol (71-36-3)	No	No	None
---------------------------	----	----	------

12. Ecological Information

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material may evaporate to a moderate extent. When released to water, this material is expected to quickly evaporate. When released into water, this material is expected to readily biodegrade. This material has a log octanol-water partition coefficient of less than 3.0. This material is not expected

to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photo chemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life between 1 and 10 days.

Environmental Toxicity:

The LC50/96-hour values for fish are over 100 mg/l. The EC50/48-hour values for daphnia are over 100 mg/l. This material is not expected to be toxic to aquatic life.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or disposed in a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name : BUTANOLS
Hazard Class : 3
UN/NA : UN1120
Packing Group : III

International (Water, I.M.O.)

Proper Shipping Name : BUTANOLS
Hazard Class : 3
UN/NA : UN1120
Packing Group : III

15. Regulatory Information

Manufacture, Storage and Import of Hazardous Chemicals Rule, 1989.

16. Other Information

NFPA Ratings: Health: **1** Flammability: **3** Reactivity: **0**

Label Hazard Warning:

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN. AFFECTS CENTRAL NERVOUS SYSTEM. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. MAY AFFECT LIVER AND

KIDNEYS.

Label Precautions:

Keep away from heat, sparks and flame.

Keep container closed.

Avoid breathing vapor or mist.

Use only with adequate ventilation.

Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Label First Aid:

If swallowed, induce vomiting immediately as directed by medical personnel.

Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. In all cases call a physician.

Disclaimer:

The information and recommendations contained herein are, to the best of **Pon Pure Chemicals Group** knowledge and belief, accurate and reliable as of the date issued. You can contact **Pon Pure Chemicals Group** to ensure that this document is the most current available from **Pon Pure Chemicals Group**. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.