

MATERIAL SAFETY DATA SHEET (MSDS) - BUTYL ACETATE

1. Product Identification

Synonyms: 1-Butyl acetate; butyl ethanoate; acetic acid, n-butyl ester

CAS No.: 123-86-4

Molecular Weight: 116.16

Chemical Formula: C₆H₁₂O₂

COMPANY IDENTIFICATION

Supplier:

Pon Pure Chemicals Group

CHENNAI, TAMILNADU, INDIA

24 Hour Health Emergency

(91) 8939878447

(91) 9444038694

Transportation Emergency Phone

(91) 8939768680

Company Name	Place	EMERGENCY TELEPHONE NUMBER
Pon Pure Chemicals Group	India	Day Emergency – 044-26161803-26161809

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
n-Butyl Acetate	123-86-4	90 - 100%	Yes

3. Hazards Identification

Emergency Overview

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED OR INHALED. CAUSES SEVERE IRRITATION TO EYES. CAUSES IRRITATION TO SKIN AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

Health Rating: 2 - Moderate (Life)

Flammability Rating: 2 - Moderate

Reactivity Rating: 1 - Slight

Contact Rating: 3 - Severe (Life)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES; CLASS B EXTINGUISHER

Storage Color Code: Red (Flammable)

Potential Health Effects

Inhalation:

Causes irritation to the respiratory tract. Symptoms may include coughing, shortness of breath. High concentrations have a narcotic effect.

Ingestion:

Irritant to tissues. Sore throat, abdominal pain, nausea, vomiting, diarrhea are the symptoms. Expected to have a narcotic effect. One ounce may produce severe poisoning.

Skin Contact:

This material degrades the skin. Irritation and discoloration of the skin are symptoms. Skin allergy occasionally develops. Persons who have become allergic can develop rash upon future exposure to low levels.

Eye Contact:

Vapors cause eye irritation. Splashes cause severe irritation, possible corneal burns and eye damage.

Chronic Exposure:

Repeated or prolonged skin contact may defeat the skin and produce irritation and dermatitis. Kidney and liver damage are reported in animals.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion:

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact:

Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire Fighting Measures

Fire:

Flash point : 26C (79F) CC

Auto ignition temperature : 425C (797F)

Flammable limits in air % by volume: LEL: 1.7; UEL: 7.6

Explosion:

Above flash point, vapor-air mixtures are explosive within flammable limits noted above. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

Fire Extinguishing Media:

Dry chemical, alcohol foam or carbon dioxide. Water may be ineffective. Water spray may be used to keep fire exposed containers cool.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Do Not attempt to clean empty containers since residue is difficult to remove. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, sparks, flame, static electricity or other sources of ignition: they may explode and cause injury or death. Containers of this material may be hazardous

when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

-OSHA Permissible Exposure Limit (PEL):150 ppm (TWA)

- ACGIH Threshold Limit Value (TLV)150 ppm (TWA), 200 ppm (STEL)

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details. Use explosion-proof equipment.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded, a half-face organic vapor respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece organic vapor respirator may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-face piece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Maintain eye wash fountain and quick-drench facilities in work area. Use chemical safety goggles and/or full face shield where dusting or splashing of solutions is possible.

9. Physical and Chemical Properties

Appearance : Clear, colorless liquid.

Odor : Mild, fruity odor.

Solubility : Slightly soluble in water (ca. 0.7% @ 20C)

Specific Gravity : 0.8822 at 20C/20C

pH : No information found.

% Volatiles by volume @ 21C (70F): 100

Boiling Point : 126C (259F)

Melting Point : -77C (-107F)

Vapor Density (Air=1): 4.0

Vapor Pressure (mm Hg): 15 @ 25C (77F)

Evaporation Rate (BuAc=1): 1

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

Carbon dioxide and carbon monoxide may form when heated to decomposition.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Dangerous when exposed to heat or flame; can react with oxidizing materials, strong alkalis, acids, nitrates and potassium-tert-butoxide.

Conditions to Avoid:

Heat, flames, ignition sources and incompatibles.

11. Toxicological Information

Toxicological Data:

Oral rat LD50: 10.8 g/kg;

inhalation rat LC50: 390 ppm/4H

Skin rabbit LD50: >17,600 mg/kg;

Irritant, skin rabbit (Std. Draize): 500 mg/24H, moderate. Irritant, eye rabbit: 100 mg moderate. Investigated as a reproductive effector.

Reproductive Toxicity:

Has shown teratogenic effects in laboratory animals.

-----\Cancer Lists\-----

---NTP Carcinogen---

Ingredient	Known	Anticipated	IARC Category
N-Butyl Acetate (123-86-4)	No	No	None

12. Ecological Information

Environmental Fate:

When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material may leach into groundwater. When released into the soil, this material is expected to have a half-life of less than 1 day. When released into water, this material is expected to readily biodegrade. When released into the water, this material is

expected to have a half-life between 1 and 10 days. This material has an estimated bioconcentration factor (BCF) of less than 100. When released into the air, this material may be moderately degraded by reaction with photochemically produced hydroxyl radicals.

Environmental Toxicity:

96 Hr LC50 fathead minnow: 18 mg/L (flow-through);

96 Hr LC50 bluegill: 100 mg/L (Static);

96 Hr EC50 freshwater algae (*Scenedesmus subspicatus*): 320 mg/L;

48 Hr EC50 water flea: 44 mg/L.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: BUTYL ACETATES

Hazard Class: 3

UN/NA: UN1123

Packing Group: III

International (Water, I.M.O.)

Proper Shipping Name: BUTYL ACETATES

Hazard Class: 3

UN/NA: UN1123

Packing Group: III

15. Regulatory Information

Manufacture, Storage and Import of Hazardous Chemicals Rule, 1989.

16. Other Information

NFPA Ratings: Health: **2** Flammability: **3** Reactivity: **0**

Label Hazard Warning:

WARNING! FLAMMABLE LIQUID AND VAPOR. HARMFUL IF SWALLOWED OR INHALED.

CAUSES SEVERE IRRITATION TO EYES. CAUSES IRRITATION TO SKIN AND RESPIRATORY TRACT. AFFECTS CENTRAL NERVOUS SYSTEM.

Label Precautions:

Keep away from heat, sparks and flame.
Keep container closed.
Use only with adequate ventilation.
Avoid contact with eyes, skin and clothing.
Wash thoroughly after handling.
Avoid breathing vapor.

Label First Aid:

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. In all cases, get medical attention.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

The information and recommendations contained herein are, to the best of **Pon Pure Chemicals Group** knowledge and belief, accurate and reliable as of the date issued. You can contact **Pon Pure Chemicals Group** to ensure that this document is the most current available from **Pon Pure Chemicals Group**. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted.